

# Jet Dryer FORCE

**ANTIVANDAL provedení do frekventovaných provozů. Vysoušeč v bílém, černém ABS plastu nebo kartáčované nerez.**



EAN: 8596220014023  
**201,23 €**  
163,60 € excluding VAT



EAN: 8596220014078  
**201,23 €**  
163,60 € excluding VAT



EAN: 8596220014061  
**246,49 €**  
200,40 € excluding VAT

## Jet Dryer FORCE - the power you can feel

Jet Dryer FORCE is a powerful hand dryer designed for high-traffic areas where speed, reliability, and durability are essential. This model combines a strong motor, robust construction, and modern design. Therefore, it is perfectly suited for public spaces, commercial properties, office buildings, and foodservice operations.

### Maximum performance, minimum wait

Jet Dryer FORCE achieves an airspeed of up to 150 m/s, ensuring quick hand drying in up to 15 seconds. Despite its performance, it maintains low noise levels and comfortable usage. The airspeed is optimized to prevent uncomfortable sensations on the skin while providing maximum efficiency.

### Touchless and hygienic

The operation of the Jet Dryer FORCE is fully automatic using an infrared sensor. No more pressing buttons – just place your hands under the dryer. Touchless operation is hygienic and comfortable, plus it reduces wear and tear on the device. The simple shape of the body also facilitates cleaning and prevents

dirt accumulation. The Jet Dryer FORCE is equipped with a HEPA filter, ensuring that the air blown onto your hands is always maximally hygienic and safe. The HEPA filter captures up to 99.97% of bacteria, viruses, and other small particles.

### **Durable construction for demanding environments**

Jet Dryer FORCE is available in a brushed stainless steel finish or durable white or black ABS plastic. It is therefore suitable for environments where there is an increased risk of vandalism or rough handling. The housing made of 304 stainless steel ensures long life and easy maintenance.

### **Intelligent air heating**

Like other Jet Dryer models, the dryer is equipped with a smart air heating system. If the ambient temperature is below 25 °C, the heating automatically activates, and it turns off at higher temperatures, thereby saving energy.

### **Background and service**

Welt Servis spol. s r.o. keeps this model and spare parts in stock at all times and provides warranty and post-warranty service. Quick availability, technical support, and long-term reliability are a matter of course for us.

### **Parts of the packaging:**

- Allen key
- 5 x 25 mm self-tapping screw, 4 pieces
- 5 mm anchor 4 pieces
- Instructions

# Parameters

## Basic parameters

|                     |                                      |
|---------------------|--------------------------------------|
| Model:              | Jet Dryer FORCE                      |
| Use:                | Suitable for all types of operations |
| Product TARIC code: | 85163300                             |
| Warranty:           | 3                                    |

## Technical parameters

|                                 |                                                                      |
|---------------------------------|----------------------------------------------------------------------|
| Mounting method - installation: | on the wall                                                          |
| Noise - sound level:            | 70 dB                                                                |
| Surface finish - color:         | Bílý ABS plast lesklý / černý ABS plast matný / Kartáčovaný nerez    |
| Controls:                       | No                                                                   |
| Status indication:              | No                                                                   |
| Boot system:                    | Automatic- infrared                                                  |
| Trigger distance:               | 15-20 cm                                                             |
| Warm air:                       | Automatically based on ambient temperature / permanently on below 25 |
| Air Speed:                      | 150 m/s                                                              |
| UV sterilization:               | No                                                                   |
| Type:                           | hot air                                                              |
| Case material:                  | ABS plastic                                                          |
| Standard air filter:            | HEPA filtr H13                                                       |

## Protective and security elements

|                                                                   |                           |
|-------------------------------------------------------------------|---------------------------|
| Protection against excessive use:                                 | Yes                       |
| Overcurrent protection, overheating and short-circuit protection: | Yes                       |
| Electricity class protection:                                     | I. (protective conductor) |
| Degree of protection:                                             | IPX1                      |

## Electric specifications

|                         |                      |
|-------------------------|----------------------|
| Input voltage:          | AC 220-240 V         |
| Frequency:              | 50/60 Hz             |
| Power input:            | 1300 W               |
| Heating element output: | 900 W                |
| Motor power:            | 400 W                |
| Motor type:             | Serial AC commutator |
| Current consumption:    | 6 A                  |
| Standby mode:           | <2 W                 |
| Power cable:            | CEE plug 7/7         |
| Power cord length:      | 65 cm                |

## Dimensions, weight, packaging

|                                  |                                                                             |
|----------------------------------|-----------------------------------------------------------------------------|
| Device dimensions:               | 390x234x142 mm (h/w/d)                                                      |
| Device weight:                   | ABS - 3.7 kg / Brushed stainless steel - 4.7 kg                             |
| Packaging dimensions:            | 435x280x185 mm (h/w/d)                                                      |
| Weight including packaging (kg): | Black ABS plastic: 3.7, White ABS plastic: 3.7, Rolled stainless steel: 4.7 |
| Packing method:                  | Protective polybag, polystyrene cover, cardboard box                        |
| Width of the packaging (cm):     | 28                                                                          |
| Height of packaging (cm):        | 43.5                                                                        |
| Depth of packaging (cm):         | 18.5                                                                        |

