# **Jet Dryer SLIM**

S LED diodami, 2 rychlostmi sušení, systémem Dry Floor (pro zachytávání odkapové vody) a Hepa filtrem



#### **Small dimensions**

Slim is a compact jet dryer from the Jet Dryer Series. It is ideal where you are limited by space. Despite its small dimensions, it will amaze you with its drying power.

## **Dual jets for fast hand drying**

A total of 23 nozzles are distributed on both sides of the drying area. The hands are dried evenly and in record-breaking short time.

#### Blue backlight

The inner drying space is illuminated by energy-saving LED diodes. The muted dark blue light gives a modern touch and shows the user where to place their hands.

#### 2 speeds

With the SLIM jet dryer, you can choose between two drying speeds. On the lower setting, the operation of the dryer is very quiet. On the higher setting, the drying time is shorter.

You can conveniently switch speeds on the control panel at the top of the hair dryer.

## **Automatic air heating**

The hairdryer is equipped with a sensor of the surrounding temperature, and the air heating automatically turns on when the temperature drops.

#### **Dry Floor**

The Dry Floor system ensures that the floor under the dryer will always be dry. The Slim jet dryer is equipped with a water tank.

## Hygienic hand drying

The operation of the dryer is completely contactless, so there is no cross-contamination. The sucked air is filtered through a HEPA filter. The HEPA filter eliminates more than 99.97% of fine dust particles with a size of 300 nanometers.

#### Air freshener

The gel air freshener can be purchased additionally. Subsequently, a pleasant scent is released during the operation of the dryer.

Welt Servis spol. s r.o. keeps products and spare parts in stock and provides both warranty and post-warranty <u>service</u>.

## Parts of the packaging:

- Assembly instructions
- Assembly suspension panel
- 5 mm anchor 6 pcs
- Power cable
- 4 x 25 mm self-tapping screw 6 pcs

# **Parameters**

## **Basic parameters**

| Basic parameters  |  |
|---|--|
| Model:  | Jet Dryer SLIM   |
| Use:  | Ideal for all types of commercial use, also suitable for space limited toilets |
| Warranty:   | 3 years  |
| Product TARIC code:   | 85163300   |
| Technical parameters  |  |
| Mounting method - installation:                                   | Wall   |
| Noise - sound level:  | 70 dB  |
| Case material:  | ABS plastic  |
| Surface finish - color:   | White colored plastic / silver varnish   |
| Controls:   | Capacitive buttons   |
| Status indication:  | LEDs   |
| Drying chamber lighting:  | Blue LED Lighting  |
| Trigger System (Power On, Control):                               | Automatic-infrared sensor  |
| Warm air:   | YES - according to ambient temperature / permanently on                        |
| Air preheating:   | No   |
| Change engine speed / air speed:                                  | Two air speed settings   |
| Air flow:   | 23.5-29 l / s  |
| Air Speed:  | 85-105 m / s   |
| Dry Floor system:   | Yes - drip tray  |
| Drip tray volume:   | 500 ml   |
| Number of uses until the drip tray is filled:                     | 650  |
| Operating temperature:  | -10 °C / + 40 °C   |
| UV sterilization:   | No   |
| Standard air filter:  | No   |
| HEPA filter:  | Yes  |
| Type:   | Sparkling  |
| HEPA filter class:  | E12  |
| Electric specifications   |  |
| Input voltage:  | AC 220-240 V   |
| Frequency:  | 50/60 Hz   |
| Power input:  | 1800-2000 W  |
| Heating element output:   | 900 W  |
| Motor power:  | 900-1100 W   |
| Motor type:   | Serial AC commutator   |
| Current consumption:  | 9A   |
| Standby mode:   | <2 W   |
| Power cable:  | CEE plug 7/7, IEC-320-C13 connector  |
| Power cord length:  | 120 cm   |
| Protective and security elements                                  |  |
| Protection against excessive use:                                 | Automatic engine shutdown after 25 s   |
| Overcurrent protection, overheating and short-circuit protection: | Yes  |
| Electricity class protection:                                     | I. (protective conductor)  |
| Degree of protection:  Dimensions, weight, packaging              | IPX4   |
| Device dimensions:  | 566x296x164 mm (h / w / d)   |
| Device difficults:  | JUUXZ 3UX 104 111111 (11 / W / U)  |

| Device weight:                   | 6.5 kg   |
|----------------------------------|--|
| Weight including packaging (kg): | 8 kg   |
| Packaging dimensions:            | 610x360x260 mm (h / w / d)                           |
| Packing method:                  | Protective polybag, polystyrene cover, cardboard box |
| Width of the packaging (cm):     | 36   |
| Height of packaging (cm):        | 61   |
| Depth of packaging (cm):         | 26   |































