

VinoTek II. JAKOST VT2

VYSTAVENO/ROZBALENO - více informací v popisu



EAN: 8596220003096x

485,40 €

404,50 € bez DPH

II. jakost

Přístroj byl využíván při prezentacích a výstavách. Mírné oděrky, na boční straně mírná prohlubeň. Pant spodních dvířek lehká koroze. Fotografie v příloze

The automatic wine dispenser VinoTek VT2 is designed for two wine bottles. This model is equipped with an input for an external supply of preservative gas.

Thanks to its compact size, it is suitable for smaller gastronomy operations that want to promote the sale of quality wine. Hesitant customers can taste the wine before purchasing the whole bottle.

Even wine connoisseurs at home will appreciate the benefits of the VinoTek system. You don't have to finish a whole bottle the same evening you opened it.

VinoTek maintains a constant internal temperature, so your wine will always be properly chilled. Current temperature information is displayed on the backlit LED display.

The main advantage of the VinoTek system compared to wine fridges is the ability to preserve the quality characteristics of wine for up to 30 days after opening. This is achieved through a protective argon atmosphere.

VinoTek VT2 contains an internal [gas cartridge with a volume of 0.2l](#). This volume is sufficient for approximately 25 bottles of wine.

Compared to VinoTek VT2i, it is possible to connect an additional cartridge or large gas cylinders through an external input.

External connection will allow you to easily replace the cartridge without the need to handle the VinoTek. You can easily integrate it into furniture. Switching between the internal/external food-grade argon source is set by pressing a single button.

You determine the size of one serving of wine yourself.

With just one press of a button, the automatic dispenser will give you 1-99 ml (a small sip or even a whole glass). VinoTek allows you to set the dose approximately per 1 ml.

- Dispenser capacity: 2 wine bottles
- Adjustable temperature range 7-18 °C
- Approximate dosage setting of wine volume per 1ml. Dosage of wine after the set volume or by spray.
- Blue LED display showing the temperature.
- Internal LED lighting with the option to turn on/off.
- Internal gas cartridge
- Entry to external gas cartridge
- Option to connect a standard pressure bottle.

Parts of the packaging:

- 2x [0.2l gas cartridge](#) (two cartridges last for approximately 50 bottles of wine)
- Power cable
- External cartridge connection kit (hose, control valve).
- User Manual

Parameters

Basic parameters

| | |
|------------------|-------------|
| Model: | VinoTek VT2 |
| Warranty period: | 2 years |

Technical parameters

| | |
|--|---|
| Mounting method - installation: | Free-standing, height-adjustable feet |
| Noise - sound level at 1m: | 39 dB |
| Controls: | Buttons, rocker switches |
| Housing material - case: | Plastic / metal / glass |
| Surface finish - color: | Powder-coated matt black, Rubberized plastic |
| Dispenser capacity: | 2 bottles of wine |
| Max. size of wine bottle: | 350 x 90 mm (h / w) |
| Wine preservation time: | Argon - up to 50 days, nitrogen - up to 30 days |
| Setting the amount of dispensed wine: | Optional by 1 ml increments (1-99 ml) |
| Setting the cooling temperature range: | 7-18 ° C |
| Operating temperature: | 7-32 ° C |
| Top drip tray: | No |
| Drip tray: | No |
| Interior lighting: | White LED Option On / Off |
| Separate cooling: | No |
| Cooling medium: | R134a |
| Preservative and propellant medium: | Argon 99.96% (Nitrogen E 941) |
| Min. / max internal working pressure: | 0,6 bar (9 PSI) / 3,1 bar (45 PSI) |
| Internal gas cartridge: | Yes |
| Connectable external cartridge: | Yes |
| Connectable Standard Bottle (200-300 bar): | Yes- via a pressure reducer at 0.6-3.1 bar per instrument input |
| Cartridge filling pressure: | 120 bar |
| Cartridge (s): | 0.2 l |
| The amount of gas in the cartridge: | 25 g |
| Number of wine bottles per cartridge: | Approx. 25 pcs |

Electric specifications

| | |
|--------------------|--------------|
| Input voltage: | AC 220-240 V |
| Frequency: | 50/60 Hz |
| Power input: | 85 W |
| Power cable: | CEE plug 7/7 |
| Power cord length: | 175 cm |

Protective and security elements

| | |
|---|---------------------------|
| Overcurrent protection, short circuit protection: | Yes |
| Pressure relief valves: | Yes |
| Electricity class protection: | I. (protective conductor) |

Dimensions, weight, packaging

| | |
|-----------------------|--|
| Device weight: | 18.6 kg |
| Device dimensions: | 605 x 235 x 367 mm (h / w / d) |
| Packaging dimensions: | 640 x 290 x 450 mm (h / w / d) |
| Packing method: | Protective polybag, polystyrene cover, cardboard box |

